

Silo Weighing System

S Series



Flexible Weighing System for Your Process Needs

FEATURES

- Modern intuitive system that supports up to 24 silos
- Low uncertainty weighing and temperature measurements
- Configurable flexible system for your process needs
- 3 possible display controllers: ST1, ST3 and S-Box
- Remote or local interface
- Plug and play DIN rail module for easy replacement
- Powerful 32-bit x 86 microprocessor (ST3 and S-Box)
- Multi-lingual menu available (ST3 and S-Box)
- Universal Power Supply rating of 90/230 VAC to 24 VDC



STANDARD OPTIONS

- Modbus/TCP option (ST1)
- Ethernet/IP option (ST3 and S-Box)
- Relay output option as limit switches for process variables monitoring (weighing and temperature)
- Up to 48 PT100 temperature sensors

Low Uncertainty and High Repeatability Weighing System

The Silo Weighing System S Series offers a cost-effective solution to accurately measure the weight of process variables (PV) within a silo. This provides a better measurement than percentage of filling. Our innovative solution guarantees precise PV management while making it very easy for operators to monitor the storage level and temperature of PV stored in a silo. Adapting with the 178 extensometer and controllers ST1, ST3 and S-Box, this system provides repeatable weighing and temperature measurements.

The controllers are appropriate for a wide range of industrial and commercial applications ranging from agriculture, cement plant, food & beverage industry, water treatment plant, etc.

The ST1 features an LCD screen with 4 buttons which is able to display up to 4 measurements per screen. The ST3 has an intuitive touch screen that is easy to use and can display up to 24 measurements per screen (8 weighing measurements plus 16 temperature measurements). The S-Box is appropriate for centralizing many measurements on one interface (website). Its website is easy to use and permits up to 5 users to monitor measurements from any computer connected to the same network.

Specifications Table

Indicator	ST1 system	ST3 system	S-Box system
Load Cell	178	178	178
Silo Number	Up to 8	Up to 24	Up to 24
Temperature Sensors	Up to 16	Up to 48	Up to 48
Display Measurement per Screen	Up to 4	Up to 24	Up to 72
Maximum Settable Screen Pages per System	Up to 6	Up to 3	N/A

At VPG Transducers, we understand that
each application can be unique or special.

Please contact our in-house Custom Solutions team to
engage our services towards meeting your specific requirements:

vpgt.customsolutions@vpgsensors.com

DISCLAIMER: ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE. Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product. The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein. VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.** Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com. No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG. The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications. Product names and markings noted herein may be trademarks of their respective owners.